



RB-30 30", 2.5 kg Ring Buoy Technical Sheet

Model No: RB30
U.S.C.G. Appr# 160.050/131/0

Manufacturer: Taylortec, Inc.
16152 East Club Deluxe Rd.
Hammond, LA 70403 USA
+ 1 985 542 6266

Description: Type IV, Throwable Device, Orange Life Ring Buoy, 30", 2.5 kg. The shell is made of high impact linear low-density polyethylene that is U.V. stabilized. With 100% foam filling, the buoy will not absorb water if torn or punctured. The floating polypropylene grab-line can be easily replaced in the field. SOLAS Grade Reflective Tape is optional.



Materials: Filling is two-part expandable polyurethane foam. Outer hard shell is low density polyethylene. UV resistant 3/8" hollow braid polypropylene black rope. SOLAS Grade Reflective tape is optional. All materials are U.S.C.G. approved.

Color: International Orange

Buoyancy: Exceeds U.S.C.G. minimum required 32 lb

Weight: 2.5 kg, (7.5 lb)

Dimensions: Outer Diameter: 29.5 +/- 1.50"
Inner Diameter: 18.00 +/- 00.9"
Width: 5.81 +/- 0.30"
Depth: 4.19 +/-0.21"
Wall Thickness: Avg 0.154" (0.12" min)

Packing: 3 ring buoys per box

Pricing: Price is based on quantity breakdown, and whether with or without reflective tape

Instructions: Rescuer should grab the throwline bag in one hand and the ring buoy with the throwing arm. Check wind and current and throw ring buoy with a side arm motion to the front of the victim. The throw line is not meant to lift the victim out of the water.

Please visit our website: www.taylortec.com for more information