



WV-9D Welders Safety Fall Vest Technical Sheet

Model No: WV-9D

U.S.C.G. App# 160.053/95/0

Manufacturer: Taylortec, Inc.
16152 East Club Deluxe Rd
Hammond, LA 70403 USA
+ 1 985 542 6266

Description: Type V, Welding Ready Fall Vest. Flame resistant, inherently buoyant, 3-piece fabric covered foam work vest with pocket. This work vest has a slot in the back to facilitate wearing over a fall restraint harness. When worn with a harness, adjust harness for proper fit with "D" ring located in the middle upper back. Don life jacket over harness and place "D" ring through slot in back pad of life jacket. Adjust back pad using the aluminum slides to line up slot with "D" ring. Keep front fastened and adjust for snug fit. Attach lifeline to back "D" ring if required.



Materials: PVC-based closed cell foam, polyester cotton fiber pigmented with flame resistant acrylic top coating, 1" olive green cotton webbing with fire retardant sizing, aluminum slides, stainless steel snaphooks. All materials are U.S.C.G. approved.
Features available: reflective tape (RT), custom silk screen stenciling.

Color: International Orange

Buoyancy: Minimum required 17.5 ± ½ lb, our design exceeds this minimum requirement.

Weight: 1.85 lb

Thickness: 1 5/8" thick (± ¼") pads

Dimensions: Front pieces: 15" L x 11" W
Back piece: 13" L x 11" W

Packing: 10 work vests per box.
Pieces are stacked together and enclosed in a clear plastic bag, ~6" in height.

Vest Size:

	L	1XL	2XL	3XL
Chest Size	56"	62"	68"	74"

Chest size is increased by 6" for each XL. Shoulder and waist straps are also increased accordingly, and are adjustable. More XL sizes are available on request.

Instructions for donning and caring for your PFD can be found on our website: www.taylortec.com